

Cast Iron Gate Valve - PN6 Flanged

Flanged PN6, GG25 Body, Cast Brass Seat, Brass Stem, Inside Screw, Non-rising Stem

Pressure/Temperature Rating

Pressure	PN10 Rated
Temperature	-10°C to 80°C

Specifications

DN	F	L	H	Kg
50	165	150	245	11.0
65	185	170	277	15.0
80	200	180	300	18.0
100	220	190	341	23.0
125	250	200	404	31.0
150	285	210	453	41.0
200	340	230	534	63.0

Material List

1.	Screw	Zinc Plated Carbon Steel
2.	Washer	Zinc Plated Carbon Steel
3.	Handwheel	Cast Iron
4.	Packing Gland	Cast Iron
5.	Packing	PTFE
6.	Stuffing Box	Cast Iron
7.	Gasket	SBR Rubber
8.	Stem	Brass
9.	Bonnet	Cast Iron
10.	Gasket	SBR Rubber
11.	Motherscrew	Cast Brass
12.	Wedge	Cast Brass DN40 to DN100 Cast Iron DN125 to DN200
13.	Seat	Cast Brass
14.	Body	Cast Iron
15.	Nut	Carbon Steel
16.	Screw	Carbon Steel
17.	Tie Rod	Carbon Steel

